```
No.     Time        Source                Destination           Protocol Info
      8 12.124060   128.179.67.76         212.249.15.4          SIP/SDP  Request: INVITE s
ip:+41216939263@212.249.15.4, with session description

Frame 8 (786 bytes on wire, 786 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 128.179.67.76 (128.179.67.76), Dst: 212.249.15.4 (212.249.15.4)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: INVITE sip:+41216939263@212.249.15.4 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>
    Contact: <sip:+41216939299@128.179.67.76>
    Supported: replaces
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 INVITE
    User-Agent: Grandstream BT110 1.0.8.33
    Max-Forwards: 70
    Allow: INVITE,ACK,CANCEL,BYE,NOTIFY,REFER,OPTIONS,INFO,SUBSCRIBE
    Content-Type: application/sdp
    Content-Length: 236
  Message body
```

```
No.     Time        Source                Destination           Protocol Info
      9 12.124261   212.249.15.4          128.179.67.76         SIP      Status: 100 Givin
g a try

Frame 9 (353 bytes on wire, 353 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 100 Giving a try
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 INVITE
    Server: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     10 12.124328   195.129.125.74        212.190.89.137        SIP/SDP  Request: INVITE s
ip:+41216939263@212.190.89.137, with session description

Frame 10 (1063 bytes on wire, 1063 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: INVITE sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Record-Route: <sip:195.129.125.74;r2=on;lr=on;ftag=07a4b9e33ee1c051>
    Record-Route: <sip:212.249.15.4;r2=on;lr=on;ftag=07a4b9e33ee1c051>
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>
    Contact: <sip:+41216939299@128.179.67.76>
    Supported: replaces
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 INVITE
    User-Agent: Grandstream BT110 1.0.8.33
    Max-Forwards: 69
    Allow: INVITE,ACK,CANCEL,BYE,NOTIFY,REFER,OPTIONS,INFO,SUBSCRIBE
    Content-Type: application/sdp
    Content-Length: 236
    Remote-Party-ID: <sip:++41216939299@212.249.15.4>;privacy=off;screen=yes
  Message body
```

```
No.     Time        Source                Destination           Protocol Info
     11 12.164264   212.190.89.137        195.129.125.74        SIP      Status: 100 tryin
g fast

Frame 11 (626 bytes on wire, 626 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 100 trying fast
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 INVITE
    Server: OpenSer (1.2.0-dev1-notls (sparc64/solaris))
    Content-Length: 0
    Warning: 392 212.190.89.137:5060 "Noisy feedback tells:  pid=719 req_src_ip=195.129.125.74
     req_src_port=5060 in_uri=sip:+41216939263@212.190.89.137 out_uri=sip:+41216939263@212.190
    .89.137 via_cnt==2"
```

```
No.     Time        Source                Destination           Protocol Info
     12 12.214685   212.190.89.137        195.129.125.74        SIP      Status: 100 tryin
g -- your call is important to us

Frame 12 (662 bytes on wire, 662 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 100 trying -- your call is important to us
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 INVITE
    Server: OpenSer (1.2.0-dev1-notls (sparc64/solaris))
    Content-Length: 0
    Warning: 392 212.190.89.137:5060 "Noisy feedback tells:  pid=719 req_src_ip=195.129.125.74
     req_src_port=5060 in_uri=sip:+41216939263@212.190.89.137 out_uri=sip:+0101014657412169392
    63@146.188.127.1 via_cnt==2"
```

```
No.     Time        Source                Destination           Protocol Info
     15 13.204500   212.190.89.137        195.129.125.74        SIP/SDP  Status: 183 Sessi
on Progress, with session description

Frame 15 (1020 bytes on wire, 1020 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 183 Session Progress
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:54:55 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow: UPDATE
    Allow-Events: telephone-event
    Contact: <sip:+41216939263@146.188.127.1:5060>
    Record-Route: <sip:212.190.89.137;lr;ftag=07a4b9e33ee1c051>,<sip:195.129.125.74;r2=on;lr=o
    n;ftag=07a4b9e33ee1c051>,<sip:212.249.15.4;r2=on;lr=on;ftag=07a4b9e33ee1c051>
    Content-Disposition: session;handling=required
    Content-Type: application/sdp
    Content-Length: 217
  Message body
```

```
No.     Time        Source                Destination           Protocol Info
     16 13.204619   212.249.15.4          128.179.67.76         SIP/SDP  Status: 183 Sessi
on Progress, with session description

Frame 16 (993 bytes on wire, 993 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 183 Session Progress
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:54:55 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow: UPDATE
    Allow-Events: telephone-event
    Contact: <sip:+41216939263@146.188.127.1:5060>
    Content-Disposition: session;handling=required
    Content-Type: application/sdp
    Content-Length: 217
    Record-Route: <sip:212.190.89.137;lr;ftag=07a4b9e33ee1c051>
    Record-Route: <sip:195.129.125.74;r2=on;lr=on;ftag=07a4b9e33ee1c051>
    Record-Route: <sip:212.249.15.4;r2=on;lr=on;ftag=07a4b9e33ee1c051>
  Message body
```

```
No.     Time        Source                Destination           Protocol Info
     19 26.429708   128.179.67.76         212.249.15.4          SIP      Request: CANCEL s
ip:+41216939263@212.249.15.4

Frame 19 (474 bytes on wire, 474 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 128.179.67.76 (128.179.67.76), Dst: 212.249.15.4 (212.249.15.4)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: CANCEL sip:+41216939263@212.249.15.4 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>
    Supported: replaces
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 CANCEL
    User-Agent: Grandstream BT110 1.0.8.33
    Max-Forwards: 70
    Allow: INVITE,ACK,CANCEL,BYE,NOTIFY,REFER,OPTIONS,INFO,SUBSCRIBE
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     20 26.429822   195.129.125.74        212.190.89.137        SIP      Request: CANCEL s
ip:+41216939263@212.190.89.137

Frame 20 (539 bytes on wire, 539 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: CANCEL sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>
    Supported: replaces
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 CANCEL
    User-Agent: Grandstream BT110 1.0.8.33
    Max-Forwards: 69
    Allow: INVITE,ACK,CANCEL,BYE,NOTIFY,REFER,OPTIONS,INFO,SUBSCRIBE
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     21 26.429841   212.249.15.4          128.179.67.76         SIP      Status: 200 cance
ling

Frame 21 (392 bytes on wire, 392 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 200 canceling
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=f573d5f23064de02e93a9896c945de4a-0189
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 CANCEL
    Server: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     22 26.487190   212.190.89.137        195.129.125.74        SIP      Status: 200 cance
ling

Frame 22 (676 bytes on wire, 676 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 200 canceling
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=674b7ff82f05a2886431e9d401d1791a-220d
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 CANCEL
    Server: OpenSer (1.2.0-dev1-notls (sparc64/solaris))
    Content-Length: 0
    Warning: 392 212.190.89.137:5060 "Noisy feedback tells:  pid=719 req_src_ip=195.129.125.74
     req_src_port=5060 in_uri=sip:+41216939263@212.190.89.137 out_uri=sip:+0101014657412169392
    63@212.190.89.137 via_cnt==2"
```

```
No.     Time        Source                Destination           Protocol Info
     23 26.530893   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 23 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     24 26.530925   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 24 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     25 26.530974   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 25 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     26 26.551242   128.179.67.76         212.249.15.4          SIP      Request: ACK sip:
+41216939263@212.249.15.4

Frame 26 (507 bytes on wire, 507 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 128.179.67.76 (128.179.67.76), Dst: 212.249.15.4 (212.249.15.4)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.249.15.4 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Contact: <sip:+41216939299@128.179.67.76>
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 ACK
    User-Agent: Grandstream BT110 1.0.8.33
    Max-Forwards: 70
    Allow: INVITE,ACK,CANCEL,BYE,NOTIFY,REFER,OPTIONS,INFO,SUBSCRIBE
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     27 26.553087   128.179.67.76         212.249.15.4          SIP      Request: CANCEL s
ip:+41216939263@212.249.15.4

Frame 27 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 128.179.67.76 (128.179.67.76), Dst: 212.249.15.4 (212.249.15.4)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: CANCEL sip:+41216939263@212.249.15.4 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Supported: replaces
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 CANCEL
    User-Agent: Grandstream BT110 1.0.8.33
    Max-Forwards: 70
    Allow: INVITE,ACK,CANCEL,BYE,NOTIFY,REFER,OPTIONS,INFO,SUBSCRIBE
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     28 26.553140   212.249.15.4          128.179.67.76         SIP      Status: 200 cance
ling

Frame 28 (392 bytes on wire, 392 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 200 canceling
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=f573d5f23064de02e93a9896c945de4a-0189
    Call-ID: 1a5055905ce85a50@128.179.67.76
    CSeq: 9843 CANCEL
    Server: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     29 26.812577   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 29 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     30 26.812614   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 30 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     31 26.951541   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 31 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     38 27.951816   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 38 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     39 28.812739   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 39 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     40 28.812780   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 40 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     43 29.956771   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 43 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     46 32.813356   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 46 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     47 32.813397   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 47 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     50 33.958380   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 50 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     51 36.812720   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 51 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     52 36.812765   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 52 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     55 37.956169   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 55 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     56 40.812725   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 56 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     57 40.812768   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 57 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     63 41.957979   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 63 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     64 44.812710   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 64 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     65 44.812752   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 65 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     68 45.959991   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 68 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     69 48.812997   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 69 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     70 48.813054   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 70 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     73 49.962446   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 73 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     75 52.813303   212.190.89.137        195.129.125.74        SIP      Status: 487 Reque
st Cancelled

Frame 75 (491 bytes on wire, 491 bytes captured)
Ethernet II, Src: Cisco_cf:bc:41 (00:10:7b:cf:bc:41), Dst: AsustekC_fc:d3:ca (00:18:f3:fc:
d3:ca)
Internet Protocol, Src: 212.190.89.137 (212.190.89.137), Dst: 195.129.125.74 (195.129.125.
74)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0,SIP/2.0/UDP 128.179.67.76;br
    anch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     76 52.813356   195.129.125.74        212.190.89.137        SIP      Request: ACK sip:
+41216939263@212.190.89.137

Frame 76 (390 bytes on wire, 390 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_50:0e:80 (00:30:19:50:
0e:80)
Internet Protocol, Src: 195.129.125.74 (195.129.125.74), Dst: 212.190.89.137 (212.190.89.1
37)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Request-Line: ACK sip:+41216939263@212.190.89.137 SIP/2.0
  Message Header
    Via: SIP/2.0/UDP 195.129.125.74;branch=z9hG4bK23ae.b11d6374.0
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    Call-ID: 1a5055905ce85a50@128.179.67.76
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    CSeq: 9843 ACK
    User-Agent: OpenSER (1.2.0-notls (i386/linux))
    Content-Length: 0
```

```
No.     Time        Source                Destination           Protocol Info
     80 53.960131   212.249.15.4          128.179.67.76         SIP      Status: 487 Reque
st Cancelled

Frame 80 (434 bytes on wire, 434 bytes captured)
Ethernet II, Src: AsustekC_fc:d3:ca (00:18:f3:fc:d3:ca), Dst: Cisco_cf:bc:41 (00:10:7b:cf:
bc:41)
Internet Protocol, Src: 212.249.15.4 (212.249.15.4), Dst: 128.179.67.76 (128.179.67.76)
User Datagram Protocol, Src Port: sip (5060), Dst Port: sip (5060)
Session Initiation Protocol
  Status-Line: SIP/2.0 487 Request Cancelled
  Message Header
    Via: SIP/2.0/UDP 128.179.67.76;branch=z9hG4bKc34f33e50effb96b
    From: <sip:+41216939299@212.249.15.4>;tag=07a4b9e33ee1c051
    To: <sip:+41216939263@212.249.15.4>;tag=8EF49B8-1697
    Date: Wed, 23 May 2007 06:55:09 GMT
    Call-ID: 1a5055905ce85a50@128.179.67.76
    Server: Cisco-SIPGateway/IOS-12.x
    CSeq: 9843 INVITE
    Allow-Events: telephone-event
    Content-Length: 0
```